

RUBBER SHEETING PARA QUALITY 7689 — NR



INTERIOR	1	g/cm³	-25 - +70	°C	35 +/- 5	Sh A	600	%	12	MPa	1-10	mm
ENVIRONMENT	DENSITY	TEMPERATURE RANGE	HARDNESS	ELONGATION	TENSILE STRENGTH	THICKNESS						

Sealing plate high-strength and highly elastic with increased abrasion resistance. Made on the basis of natural rubber NR with various physical and mechanical properties. With the possibility of specifying the thickness (1 - 10 mm), width (1,200 - 1,400 mm) and number of inserts (0 - 2 pcs). Click and choose. Complete the exact specification in the configurator.



RESISTANCE

- Abrasion resistance **HIGHLY RESISTANT**
- Weather resistance **NO**
- Ozone resistance **NO**
- UV resistance **NO**
- Alkaline resistance **MEDIUM RESISTANT**
- Acid resistance **MEDIUM RESISTANT**
- Oil resistance **NO**
- Gasoline resistance **NO**

CONFIGURATION OPTIONS

THICKNESS

- 1 mm (+/- 0,2 mm)
- 1.5 mm (+/- 0,2 mm)
- 2 mm (+/- 0,2 mm)
- 3 mm (+/- 0,3 mm)

WIDTH

- 1200 mm (+/- 10 mm)
- 1400 mm (+/- 10 mm)

LENGTH

- 20 m (+/- 200 mm)
- 10 m (+/- 200 mm)

NUMBER OF REINFORCEMENT LAYERS

- without reinforcement (for thicknesses 1 - 10 layers mm)